PATENT COOPERATION TREATY PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Title II of the Patent Cooperation Treaty)

Applicant's or agent's file number RL 609 WO		FURTHER ACTION See Form PCT/IPEA/416				
International Application No. PCT/EP2005/001909		International filing date (day/month 24/2/2005	Priority date (day/mo 23/3/2004	nth/year)		
International Patent Classification (IPC) or national classification and IPC INV. F16L3/00 F16B37/04 F16B5/02 F16B37/08						
Applicant A. RAYMOND & CIE et al.						
 This report is the preliminary examination report that has been established by the international preliminary examining authority according to Article 35 and is being transmitted to the applicant in accordance with Article 36. 						
2. This REPORT consists of a total of 5 sheets, including this cover sheet.						
3. The report also includes ATTACHMENTS that comprise						
 a.						
	Point 4, ar	t replace previous pages, but which in the additional box, contain the International Application in	a change that goes beyon	d the disclosed		
b. (sent only to the International Office) (please indicate the type and number of this/these data carrier(s) in all, that contain(s) a sequence record and/or the associated tables, only in electronic form, as indicated in the additional box with regard to the sequence record (see Section 802 of the Administrative Regulations).						
4. This report contains data on the following points:						
⊠ Box No. I □ Box No. II □ Box No. III	Basis of th Priority Non-estab	e decision lishment of opinion with regard	to novelty, inventive step a	nd industrial		
□ Box No. IV ⊠ Box No. V	applicabilit Lack of un Substantia		2) with regard to novelty, i	nventive step and		
☐ Box No. VI ☐ Box No. VII ☐ Box No. VIII	Certain do Certain de	cuments cited fects in the international applica servations on the international a	tion	ement		
Date of submission of the request			Date of completion of this	report		
1/18/2006			5/30/2006			
Name and address of inte	ernational ex	amining authority:	Authorized officer:	Marie Company		
D-1095	an Patent O 8 Berlin 49 30 25901	ffice - Giltschlner Str. 103	Granger, H. Tel.: +49 30 25901-516			
Fax: +49 30 25901 - 840						

Box No. I Basis of the report

1.	With regard to language, the decision is based on					
	X	☑ the international application in the language in which it was submitted.				
		a tr trar	slation that was submitte international search (ac publication of the interna	onal application into the following language, which is the language of the ed for the following purpose: cording to Rules 12.3 a) and 23.1 b)) ational application (according to Rule 12.4 a)) or examination (according to Rules 55.2 a) and/or 55.3 a))		
2.	wei	With regard to the components * of the international application, the report is based on (amended pages that were presented to the Application Office on request pursuant to Article 14, are considered to have been "originally submitted" in the context of this report and are not attached to it):				
	Sp	Specification, pages				
	3-6 1, 2	6 2, 2a	ı	as originally filed received on 1/18/2006 with letter of transmittal dated 1/14/2006		
	Cla	Claims, Nos.				
	1-7	7		received on 1/18/2006 with letter of transmittal dated 1/14/2006		
	Dra	Drawings, pages				
	1/4-4/4			as originally filed		
	□ a sequence record and/or any associated tables - see additional field with regard to the sequence record					
3.		The following documents are omitted because of the amendments: Specification: page Claims: No. Drawings: page/figure Sequence record: (exact information): Any tables belonging to the sequence record (exact information):				
4.		This report was prepared without consideration (of some) of the amendments attached to this report listed below, since in the opinion of the authorities, they go beyond the disclosed content as originally submitted, for the reasons given in the additional box (Rule 70.2 c)).				
			Specification: page Claims: No. Drawings: page/figure Sequence record: <i>(exac</i> Any tables belonging to	et information): the sequence record (exact information):		

* If Point 4 applies, some or all of these pages can be given the notation "Replaced."

Box No. V Substantiated statement under Article 35(2) with regard to novelty, inventive step and industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)

Yes: Claims
No: Claims
Inventive step (IS)

Yes: Claims
Vo: Claims
Industrial applicability (IA)

Yes: Claims
Ves: Claims
No: Claims
Ves: Claims
No: Claims

NO. Ciaillis

2. Documents and explanations (Rule 70.7):

See supplemental sheet

Re Item V

Substantiated statement with regard to novelty, inventive step and industrial applicability; citations and explanations supporting such statement

The following document is cited:

D1: DE 195 33 138 C1

- Document D1 is considered to be the most similar state of the art relative to the object of Claim D1. D1 discloses a device pursuant to the preamble of <u>Claim 1</u>.
- 2. The object of <u>Claim 1</u> differs from **D1** in that "the part of the drive component (17) engaged rotationally with the screw component (11) is designed with a tool stud structure (20) that can be engaged with a hand tool."

The object of Claim 1 is therefore new (Article 33(2) PCT).

- 3. The task underlying the invention is accordingly to describe a device of the type mentioned initially with which a definite set arrangement relative to the support can be obtained with automated assembly even with radial tolerances in the positioning of threaded bolts.
- 4. The method proposed for this task in <u>Claim 1</u> of this Application is based on an inventive act (Article 33(3) for the following reasons: the method is neither disclosed nor anticipated in the prior art. The drive component (7a) in D1 is not expected to be rotated, since it adheres to the sheet metal cage (3a) from a painting process. Consequently, one skilled in the art would not provide the drive component with a hand tool.
- 5. <u>Claims 2-7</u> are dependent on <u>Claim 1</u> and thus likewise meet the requirements of the PCT with regard to novelty and inventive act.

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY (SUPPLEMENTAL SHEET) International Application PCT/EP2005/001909

PCT/EP2005/001909 A. Raymond & Cie et al. RL 609 WO January 17, 2006

1

DEVICE TO BE FASTENED TO A SUPPORT WHICH IS PROVIDED WITH A THREADED BOLT

This invention relates to a device to be fastened to a support that is provided with a threaded bolt pursuant to the preamble of Patent Claim 1.

Such a device is disclosed by DE 195 33 138 C1. In the previously known device, the screw component is screwed onto a threaded section of the threaded bolt and there is an abutment area against which the screw component rests in its final position. The screw component has a first engagement structure in the form of radially extended flat projections. There is also a rotatable part that has a second engagement structure in the form of receptacle pockets over-dimensioned radially with respect to the flat projections, which is engaged with the first engagement structure, with the screw component and the part being movable radially with respect to one another, at least before assuming the final position. The screw component is thereby mounted to float in the part.

DE 200 23 083 U1 discloses a clamp with a female fastening element that has a plurality of movable segments, which engage on the profile of a male fastening element. This produces a rotationally fixed connection between the female fastening element and the male fastening element.

PCT/EP2005/001909
A. Raymond & Cie et al.

RL 609 WO January 17, 2006

2

Other devices for fastening to a support that has a threaded bolt are known in practice and have a screw component in the form of a threaded nut that can be screwed onto a threaded section of a threaded bolt to rest against an abutment area in its final position. Cable holders connected to the previously known devices, for example, can in fact be fastened to threaded bolts, but they have the drawback that with a position relative to the support to be preserved, tolerances in the positioning of the threaded bolts cannot be compensated for, or only in extremely limited fashion, for purposes of automated assembly.

The task underlying the invention is to describe a device of the type mentioned initially, with which a definite set arrangement with respect to the support can be preserved with automated assembly, even in case of radial tolerances in the positioning of threaded bolts.

This task is accomplished pursuant to the invention by a device of the type mentioned initially with the characterizing features of Patent Claim 1.

By providing that the screw component and the drive component are engaged with one another with radial mobility and rotationally fixed, and thus the screw component is also turned by the interaction of the engagement structures when the drive component is turned by the engagement of a hand tool with the tool stud structure, radial tolerances in the positioning of the threaded bolts can be compensated for even with a set positioning relative to the support.

PCT/EP2005/001909 A. Raymond & Cie et al. RL 609 WO January 17, 2006

2/1

Other useful refinements of the invention are the object of the subclaims.

A preferred example of embodiment of the invention is described below with reference to the figures. The figures show:

- Fig. 1 an example of embodiment of the invention in a perspective exploded view that is integrated in a cable holder and that has a screw component and a drive component mounted in a ring cage,
- Fig. 2 the example of embodiment of Fig. 1 in another perspective exploded view,
- Fig. 3 the example of embodiment of Fig. 1 and Fig. 2 in a cutaway perspective view enlarged relative to the scale of Fig. 1 and Fig. 2, in the area of the screw component and the drive component, and
- Fig. 4 the example of embodiment of Fig. 1 to Fig. 3 in a cross-sectional view in the area of the screw component and the drive component in a final position of the screw component on a threaded bolt.

PCT/EP2005/001909 A. Raymond & Cie et al. RL 609 WO January 17, 2006

7

PATENT CLAIMS

- Device to be fastened to a support that is provided with a threaded bolt (23), with a screw component (11) that can be screwed onto a threaded section of the threaded bolt (23), and with an abutment area on which the screw component rests in its final position, wherein the screw component (11) has a first engagement structure (15), there is a rotatable part (17) that has a second engagement structure (19) that is engaged with the first engagement structure (15), and the screw component (11) and the part (17) are movable radially with respect to one another, at least before assuming the final position, characterized by the fact that the part designed as a drive component (17) with a tool stud structure (20) in rotationally fixed engagement with the screw component (11), can be engaged with a hand tool.
- 2. Device pursuant to Claim 1, characterized by the fact that there is a ring cage (6) that has an abutment area (7), in which the screw component (11) and/or the drive component (17) is/are held.
- 3. Device pursuant to Claim 2, characterized by the fact that the drive component (17) is held in the axial and radial directions.

PCT/EP2005/001909 A. Raymond & Cie et al.

RL 609 WO January 17, 2006

8

- 4. Device pursuant to one of the claims 1 to 3, characterized by the fact that the engagement structures have projections (15, 19) extending in the radial direction.
- 5. Device pursuant to Claim 4, characterized by the fact that outer walls (16, 21) of the projections (15, 19) pointing at one another are arched and rounded off toward the outside.
- 6. Device pursuant to one of the claims 1 to 5, characterized by the fact that the screw component (11) has at least two internal catches (13) running radially from an outer ring (12) toward one another, whose free ends can be engaged with the threaded section.
- 7. Device pursuant to Claim 6, characterized by the fact that the internal catches (13) are adjusted in funnel-like fashion in the direction of insertion of the threaded bolt (23).